



FAB Sheet – Aspect Zebra

| FEATURES | ADVANTAGES | BENEFITS |
|--|--|---|
| Choice of wattages 34-130W | Wide range of options to suit application | Optimised lighting designs reducing costs |
| LED colour temperatures: 3000K, 4000K or 5700K | Range to suit various applications | Optimised lighting |
| Projected LED lifetime L90 after 100,000 hours | Reduces maintenance | Maintenance cost and time savings |
| International Dark-Sky Association approved | Dark-skies compliant when using a colour temperature of 3000K or below at 0° degree tilt | Can be used in dark-sky applications in order to protect the night sky from light pollution |
| High quality LM6 aluminium alloy body with polyester powder coat. Stainless steel fixings and inserts. | Strong product 1000 hour salt spray resistant | High durability Corrosion resistant – longer lasting luminaire |
| Toughened flat glass cover | Vandal resistant | Less repair works/costs |
| Replaceable gear tray without the need for tools | Easily serviceable Simple to upgrade Easy access | Provides a long-term installation Minimal future costs No tools required |
| PMMA lenses | High light transmission Durable material | Clear lighting Longer life |
| CLO (constant light output) available | Lumen output remains at 100% for 100,000 hrs | Energy savings Reduced maintenance Cost savings |
| PowerSet feature (integral lumen and power output selection device) | Easy onsite adjustment No re-programming required | Reduced stock holding Less disruption Time and cost savings |
| Optional dimming and lighting controls | Variable controls Simple upgrades | Increased levels of energy savings Minimal future costs |
| IK08 and IP66 ratings | High impact resistance and ingress protection No dust traps | Longer life Less repair works and costs Easier maintenance |
| UMSUG coded | Separate meter not needed - charging can be included in authorities' overall inventory and single bill | Reduced administration |
| Manufactured in Britain | Parts required are readily available | Quicker resourcing and assistance |
| Minimum 10 year warranty | Risk to the contractor and client is reduced | Peace of mind from the backing of an established manufacturer |