



FAB Sheet – I-Range

FEATURES	ADVANTAGES	BENEFITS
Choice of wattages 67-340W	Wide range of options to suit application	Optimised lighting designs reducing costs
LED colour temperatures: 3000K or 4000K (<i>alternatives available</i>)	Range to suit various applications	Optimised lighting
Projected LED lifetime L90 after 100,000 hours	Reduces maintenance	Maintenance cost and time savings
500mm, 700mm and 1300mm lengths	Wide range of options to suit application	Optimised lighting designs reducing costs
Lightweight low-profile luminaire	Lighter to handle and lift	Easier and quicker installation
High quality marine grade aluminium	Strong body Corrosion resistant	Suitable for arduous conditions Longer lasting luminaire
Bespoke lensing arrangement with PMMA lenses	Maximised efficiency High light transmission Durable material	Reduced energy costs Clear lighting Longer life
Toughened, flat safety glass cover	Vandal resistant Wipeable surface	Less repair works/costs Easier maintenance
Wide variety of optics; Asymmetric, symmetric and counterbeam	Directional lighting	Enhanced lighting
Optional lighting controls	Variable controls	Increased levels of energy savings
IK08 and IP66 ratings	High impact resistance and ingress protection No dust traps	Longer life Less repair works and costs Easier maintenance
Pre-wired mains cable – silicone and PVC cable options available	Contractor not required to wire lantern	Time and cost savings on installation
Fixed clamp and adjustable stirrup clamp options	Secure mounting system Allows light to be positioned	No safety risk to users Optimised lighting
Manufactured in Britain	Parts required are readily available	Quicker resourcing and assistance
Minimum 5 year warranty	Risk to the contractor and client is reduced	Peace of mind from the backing of an established manufacturer
Delivered in highly sustainable packaging	More environmentally friendly	Reduced carbon footprint