



FAB Sheet – Modula F48

| FEATURES | ADVANTAGES | BENEFITS |
|--|---|--|
| Lighting module integrated in handrail | Combined handrail and lighting | A 'one stop shop' – no need to source these two items separately |
| | | Time saving |
| LED colour temperatures: 2700K, 3000K or 4000K | Range to suit various applications | Optimised lighting |
| Rated life of 50,000 hours | Long life of lighting module | Longer life Reduced replacements |
| High lux levels | Less modules required | Reduced cost |
| 48.3mm x 2mm stainless steel (grade 304 or 316) slotted handrail | Strong product Anti-corrosive | Sturdy and durable handrail Longer life |
| Handrails are bent using in-house CNC mandrel bending or mitred, fully welded and polished | No joints visible | Neat in appearance |
| Wide range of handrail finishes; Satin/brushed, bead blasted, electro polished, bespoke and standard warm- | Ability to select finish which is in keeping with the environment | Visually appealing |
| to-touch RAL polyester powder coat | Warm-to-touch coatings | User friendly |
| Lumaax antimicrobial/polycarbonate lens – clear or diffused | Antimicrobial resistant | Protection to help control odour and inhibit bacterial growth |
| Polycarbonate LED lighting module | Impact resistant material | More durable product |
| Clear, diffused or multi coloured lenses | Adapt the colour of light emitted | Colour theme suited to project |
| Back-to-back interconnecting modules | Continuous line of light | Visually appealing to user No affect to visibility |
| Asymmetric and symmetric distributions available | Directional lighting | Optimised lighting |
| Optional DALI and dimming controls | Variable controls | Increased levels of energy saving |
| Emergency feature | 3hr battery back up | Constant lighting in the event of power failure |
| Parallel connection | All modules continue to function if one fails | Uninterrupted lighting – no impact on visibility for user |
| Modules mechanically secured with vandal resistant (stainless steel | Vandal resistant | Less repair works/costs |
| 316) screws | Corrosion resistant | Longer life |
| IP66 and IK10 ratings | High impact resistance and ingress protection | Longer life Less repair works and costs |
| Manufactured in Britain | Parts required are readily available | Quicker resourcing and assistance |
| 5 year warranty | Risk to the contractor and client is reduced | Peace of mind from the backing of an established manufacturer |